

Beamforming Network for 5G Application

Dr. V. V. Ratnaparkhi, Tejal Chandure, Sakshi Vaidya, Rani Ingole, Prajкта Gaoture

Department of Electronics and Telecommunication Engineering,
Shri Sant Gajanan Maharaj College of Engineering, Shegaon, India

Abstract: *A spatial filtering technique called beamforming is used to improve signals coming from a certain direction in relation to a microphone array and to reduce noise and interference coming from other directions. A wireless signal is steered towards a particular receiving device in this sort of radio frequency (RF) control. Beamforming is used in a variety of technologies, including radar, sonar, wireless communications, and acoustics. In 5G technology will be using different frequency bands but we are going to use 3.5GHz frequency (n78 band). The popularity of the n78 band is a result of its widespread availability when contrasted to lower cellular spectrum that is currently being utilised by 3G & 4G networks. The 5G NR standard created the frequency band n78.*

Keywords: Butler without crossover, Antenna, Branch line Coupler, ADS Software

REFERENCES

- [1] Liao, B., Chan, S.C., 2011. DOA estimation of coherent signals for uniform linear arrays with mutual coupling. IEEE Int. Symp. on Circuits and Systems, p.377-380. <http://dx.doi.org/10.1109/ISCAS.2011.5937581>
- [2] Liao, W.C., Chang, T.H., Ma, W.K., et al., 2011. QoS-based transmit beamforming in the presence of eavesdroppers: an optimized artificial-noise-aided approach. IEEE Trans. Signal Process., 59(3):1202-1216. <http://dx.doi.org/10.1109/TSP.2010.2094610>
- [3] Liu, D.L., Ma, W.Z., Shao, S.H., et al., 2016. Performance analysis of TDD reciprocity calibration for massive MU-MIMO systems with ZF beamforming. IEEE Common Lett., 20(1):113-116. <http://dx.doi.org/10.1109/LCOMM.2015.2499283>
- [4] Liu, G.Y., Hou, X.Y., Wang, F., et al., 2016. Achieving 3D-MIMO with massive antennas from theory to practice with evaluation and field trial results. IEEE Syst. J., 11(1): 62-71. <http://dx.doi.org/10.1109/JSYST.2015.2477503> Liu, J.,
- [5] Liu, W.J., Liu, H.W., et al., 2016. Average SINR calculation of a per symmetric sample matrix inversion beamformer. IEEE Trans. Signal Process., 64(8):2135- 2145. <http://dx.doi.org/10.1109/TSP.2015.251252>
- [6] Ta, S. X., Choo, H., & Park, I. (2017). Broadband Printed-Dipole Antenna and Its Arrays for 5G Applications. IEEE Antennas and Wireless Propagation Letters, 16, 2183– 2186. doi:10.1109/lawp.2017.2703850
- [7] M. Khalily, R. Tafazolli, T. A. Rahman and M. R. Kamarudin, "Design of Phased Arrays of Series-Fed Patch Antennas with Reduced Number of the Controllers for 28- GHz mm-Wave Applications," in IEEE Antennas and Wireless Propagation Letters, vol. 15, pp. 1305-1308, 2016.
- [8] Khan, M. T., Qi Lin, X., Chen, Z., Xiao, F., Yan, Y. H., & Khalil Memon, A. (2019). "Design and Analysis of A Microstrip Patch Antenna for Water Content Sensing," 2019 16th International Computer Conference on Wavelet Active Media Technology and Information Processing.
- [9] Habaebi, M. H., Janat, M., Islam, M. R., & Hamida, B.A. (2016). "Phased array antenna metamaterial-based design operating in millimeter wave for 5G mobile networks," 2016 IEEE Student Conference on Research and Development.