

Novel Hybrid MPPT Technique for Partially Shaded Photovoltaic Arrays-A review

Sumit Gavhale¹ and Vaishali Malekar²

Students, Department of Electrical Engineering¹

Assistant Professor Department of Electrical Engineering²

Abha Gaikwad college of Engineering And Technology, Nagpur, India

Abstract: *This paper introduces a Review on hybrid MPPT control for photovoltaic (PV) arrays working under partial shading conditions. In This new algorithm will combine a traditional MPPT algorithm, such as perturb and observe, with the artificial neural network (ANN) technique. The proposed hybrid MPPT algorithm is based on the ANN and used to predict the global MPP region by estimating its voltage boundaries. Consequently, the conventional MPPT algorithm searches for the MPP in the predicted region. This technique increases the output power level of the PV array under various shading patterns. The proposed technique is modelled and simulated using MATLAB/Simulink.*

Keywords: Hybrid MPPT, ANN , P&O

REFERENCES

- [1] M. Kermadi, Z. Salam, J. Ahmed and E. M. Berkouk, "An Effective Hybrid Maximum Power Point Tracker of Photovoltaic Arrays for Complex Partial Shading Conditions," in *IEEE Transactions on Industrial Electronics*, vol. 66, no. 9, pp. 6990-7000, Sept. 2019, doi: 10.1109/TIE.2018.2877202.
- [2] B. R. Peng, K. C. Ho, and Y. H. Liu, "A Novel and Fast MPPT Method Suitable for Both Fast Changing and Partially Shaded Conditions," *IEEE Transactions on Industrial Electronics*, vol. 65, no. 4, pp. 3240- 3251, 2018.
- [3] K. S. Tey, S. Mekhilef, M. Seyedmahmoudian, B. Horan, A. M. T. Oo, and A. Stojcevski, "Improved Differential Evolution-based MPPT Algorithm using SEPIC for PV Systems under Partial Shading Conditions and Load Variation," *IEEE Transactions on Industrial Informatics*, 2018.
- [4] N. Kumar, I. Hussain, B. Singh and B. K. Panigrahi, "Single Sensor-Based MPPT of Partially Shaded PV System for Battery Charging by Using Cauchy and Gaussian Sine Cosine Optimization," in *IEEE Transactions on Energy Conversion*, vol. 32, no. 3, pp. 983-992, Sept. 2017, doi: 10.1109/TEC.2017.2669518.
- [5] Cheng-Yu Tang, Shih-Hsun Lin and Sheng-Yuan Ou, "Design and implementation of a hybrid maximum power point tracker in solar power system under partially shaded conditions," 2017 IEEE 3rd International Future Energy Electronics Conference and ECCE Asia (IFEEEC 2017 - ECCE Asia), Kaohsiung, 2017, pp. 900-905, doi: 10.1109/IFEEEC.2017.7992160
- [6] X. Zhu, S. Liu, Y. Wang, L. Dou and J. Cai, "A sliding mode control based maximum power point tracking method of PV arrays under partially shaded conditions," *International Conference on Renewable Power Generation (RPG 2015)*, Beijing, 2015, pp. 1-5, doi: 10.1049/cp.2015.0522.
- [7] Yong-Won, C., Woo-Jun, C., Jung-Min, K., et al.: 'Improved single-phase TL inverter with high power density and high efficiency for grid-connected photovoltaic systems', *IET Renew. Power Gener.*, 2016, 10, (2), pp. 166–174 [15] Li,
- [8] W., Gu, Y., Luo, H., et al.: 'Review and derivation methodology of single phase TL photovoltaic inverters for leakage current suppression', *IEEE Trans. Ind. Electron.*, 2015, 62, (7), pp. 4537–4551
- [9] Jaber, F.A., Yam, P.S., Mehran, S., et al.: 'S4 gridconnected single-phase TL inverter for PV application'. *IEEE Conf.*, 2016
- [10] Yong-Won, C., Woo-Jun, C., Jung-Min, K., et al.: 'Improved single-phase TL inverter with high power density and high efficiency for grid-connected photovoltaic systems', *IET Renew. Power Gener.*, 2016, 10, (2), pp. 166–174