

Optimized Design of Phase Vocoder for Voice Morphing

Vipin Tiwari¹ and Hitanshu Saluja²

Research Scholar, Department of Electronics & Communication Engineering¹

Assistant Professor, Department of Electronics & Communication Engineering²

School of Engineering & Technology, Soldha, Bahadurgarh, Haryana, India

Abstract: Speech is usually characterized as voiced, unvoiced or transient forms. Voiced speech is produced by an air flow of pulses caused by the vibration of the vocal cords. The resulting signal could be described as quasi-periodic waveform with high energy and high adjacent sample correlation. The two broad categories of pitch-estimation algorithms are time-domain algorithms and frequency-domain algorithms. Voice morphing is the process of producing intermediate or hybrid voices between the utterances of two speakers. It can also be defined as the process of gradually transforming the voice of one speaker to that of another. Like image morphing, speech morphing aims to preserve the shared characteristics of the starting and final signals, while generating a smooth transition between them. This paper describes the Phase vocoder method of voice morphing. We extract the feature difference of source and targeted voice applies this phase different to the source voice..

Keywords: Voice Morphing

REFERENCES

- [1]. "Analysis of a Modern Voice Morphing Approach using Gaussian Mixture Models for Laryngectomees", AmanChadha, BharatraajSavardekar, Jay Padhya, International Journal of Computer Applications (0975 – 8887) Volume 49– No.21, July 2012.
- [2]. Voice conversion: A critical survey, Anderson F. Machado, Marcelo Queiroz, 2010.
- [3]. A shape-invariant phase vocoder for speech transformation, A. Robel, September 6-10, 2010.
- [4]. Towards Morphological sound description using segmental models, JulienBloit, Nicolas Rasamimanana, September 1-4, 2009.
- [5]. A precise estimation of vocal tract parameters for high quality voice morphing, NingXu , Zhen Yang , 26-29 Oct. 2008.
- [6]. Voice Conversion Based on Maximum Likelihood Estimation of Spectral Parameter Trajectory Tomoki Toda, Member, IEEE, Alan W Black, Member, IEEE, Keiichi Tokuda, Member, IEEE, August 1, 2007.
- [7]. Ye H. and Young S., "High quality voice morphing", International Conference on Acoustics, Speech, and Signal Processing (ICASSP), 2004, Montreal, Vol. 1, 9-12.
- [8]. C. Orphanidou, I. M. Moroz, and S. J. Roberts, "Wavelet based voice morphing," in WSEAS Transactions on Systems, December 2004, vol. 3, pp. 3297–3302.
- [9]. Voice Morphing System for Impersonating in Karaoke Applications, Pedro Cano, Alex Loscos, JordiBonada, Maarten de Boer and Xavier Serra, 2000.
- [10]. Speaker Transformation Algorithm using Segmental Codebooks (STASC) ,Levent M. Arslan, 8 February 1999.
- [11]. Automatic audio morphing, Malcolm Slaney, Michele Covell and Bud Lassiter, Presented at the 1996 International Conference on Acoustics,Speech, and Signal Processing, Atlanta.
- [12]. Phase Vocoder, J.L.FLANAGAN and R.M.GOLDEN, July 18, 1966.
- [13]. Voice transformation using PSOLA technique, H. Valbret, E. Moulines, J.P. Tubach, and June 1992.
- [14]. M. Dolson, "The phase vocoder: A tutorial," Computer Music Journal, vol. 10, no. 4, pp. 14–27, 1986.
- [15]. Erro, D., Moreno, A.: Sistema de s'ntesisarm'ónico/estoc'ástico en modopitchas 'ncronoaplicado a conversi'on de voz. In: Proceedings of the IV Jornadas en Tecnolog'ia de Habla. Zaragoza (2006)

- [16]. Speaker Recognition Robustness to Voice Conversion, MireiaFarrus, Daniel Erro, and Javier Hernando.
- [17]. Automatic speaker recognition as a measurement of voice imitation and conversion MireiaFarrús, Michael Wagner, Daniel Erro and Javier Hernando.
- [18]. L. R. Rabiner , R. W. Schafer “Digital Processing of Speech Signals”.
- [19]. Yoav Meden, EyalYair and Dan Chazan, “Super Resolution Pitch Determination of Speech Signals”, IEEE TRANSACTIONS ON SIGNAL PROCESSING, VOL. 39, NO 1, JANUARY 1991.
- [20]. McAulay, R. J., Quatieri, T. F., 1986. Speech analysis/synthesis based on a sinusoidal representation. IEEE Transactions on Acoustics, Speech, and Signal Processing 34 (4), 744–754.
- [21]. Stylianou. Modeling speech based on harmonic plus noise models. In Nonlinear Speech Modeling and Apps.Springer, 2005.
- [22]. TheVocoder—Electrical Re-Creation of Speech, Homer Dudley, JSMPE; March 1940; 34 :(3) 272-278.
- [23]. Speech Coding: A Thtorial Review, ANDREAS S. SPANIAS, MEMBER, IEEE.
- [24]. Theory and Application of Digital Speech Processing, L. R. Rabiner and R. W. Schafer, June 3, 2009.
- [25]. Phase Vocoder, J.I.FLANAGAN and R.M.GOLDEN, July 18, 1966.
- [26]. An introduction to phase vocoder, John Gordon and John Strawn, Feb. 1987.
- [27]. Harmonic Sinusoid Modeling of Tonal Music Events, Wen, Xue, A thesis submitted for the degree of Doctor of Philosophy of the University of London October, 2007.
- [28]. Multiband excitation vocoder, D.W. Griffin, Aug. 1988.
- [29]. Y. Stylianou, “Harmonic plus noise models for speech, combined with statistical methods, for speech and speaker modification,” in Ph.D. dissertation, EcoleNationaledesTlcommunications, 19