

Review on Pushover Analysis Procedures

M Sam Horrison¹, Dr. Selvan V², Mr. Satheesh Kumar K. R. P³

PG Student, Department of Civil Engineering¹

Associate Professor and Head, Department of Civil Engineering²

Assistant Professor II, Department of Civil Engineering³

Kumaraguru College of Technology, Coimbatore, Tamil Nadu, India

Abstract: *Pushover analysis was the recommended method of seismic analysis before this generation. Even though Non-Linear Time History analysis is a recommended method of practice for the current generation due to its accuracy, Pushover analysis has the capability which gives much more flexibility and information on its final results. The well-known concept of 'Performance criteria', which is the specification of an acceptable level of damage to a building, can be found using this method. Using pushover analysis, it's possible to study the parent factor, which is responsible for the behaviour of buildings during seismic events. In this review, we discussed the possible lateral load combinations that can be applied during the analysis procedure and how the results can be analysed. From previous studies, it is concluded that the pushover analysis can be influenced by the geometry of the building, lateral load pattern, and the method of result evaluation.*

Keywords: Pushover analysis, Seismic evaluation, analysis procedure, Nonlinear analysis

REFERENCES

- [1]. Krawinkler, H. (1996, October). Pushover analysis: why, how, when, and when not to use it. In Proceedings of the 65th Annual Convention of the Structural Engineers Association of California (pp. 17-36).
- [2]. Krawinkler, H., & Seneviratna, G. D. P. K. (1998). Pros and cons of a pushover analysis of seismic performance evaluation. *Engineering structures*, 20(4-6), 452-464.
- [3]. Tso, W. K., & Moghadam, A. S. (1998). Pushover procedure for seismic analysis of buildings. *Progress in Structural Engineering and Materials*, 1(3), 337-344.
- [4]. FEMA-356.: Prestandard and Commentary for the Seismic Rehabilitation of Buildings American Society of Civil Engineers (2000)
- [5]. Leslie, R., & Naveen, A. (2017). A study on pushover analysis using capacity spectrum method based on Eurocode 8. In 16th World Conference on Earthquake Engineering, Reg Code: S-P148645023, Santiago, Chile.
- [6]. Goel, R. K., & Chopra, A. K. (2004). Evaluation of modal and FEMA pushover analyses: SAC buildings. *Earthquake spectra*, 20(1), 225-254.
- [7]. BIS (2002) IS 1893 (part 1): 2002—Indian standard criteria for earthquake resistant design of structures, part 1: general provisions and buildings (Fifth Revision). Bureau of Indian Standards, New Delhi
- [8]. Abhilash, R., & Biju, V. (2010). Effect of lateral load patterns in pushover analysis.
- [9]. Tokhi, A., & Arora, S. (2019). Seismic analysis and comparison of overhead intze water tank, circular water tank and rectangular water tank and response spectrum analysis. *Technology*, 10(3), 2519-2527.
- [10]. Khoshnoudian, F., Mestri, S., & Abedinik, F. (2011). Proposal of lateral load pattern for pushover analysis of RC buildings. *Computational Methods in Civil Engineering*, 2(2), 169-183.
- [11]. Pour, H. G., Ansari, M., & Bayat, M. (2014). A new lateral load pattern for pushover analysis in structures. *Earthq. Struct*, 6(4), 437-455.
- [12]. Worku, A. M., & Hsiao, P. C. (2022). An improved first-mode-based pushover analytical procedure for assessing seismic performance of special moment resisting frame building structures. *Engineering Structures*, 252, 113587.

- [13]. Kalkan, E., &Kunnath, S. K. (2004). Lateral load distribution in nonlinear static procedures for seismic design. In Structures 2004: Building on the Past, Securing the Future (pp. 1-10).
- [14]. Habibi, A., Izadpanah, M., &Namdar, Y. (2022). A new modal lateral load pattern for improving pushover analysis to estimate nonlinear responses of structures. Australian Journal of Structural Engineering, 23(4), 289-302.
- [15]. Shayanfar, M. A., Ashoory, M., Bakhshpoori, T., &Farhadi, B. (2013). Optimization of modal load pattern for pushover analysis of building structures. StructEngMech, 47(1), 119-129.
- [16]. Shakeri, K., Shayanfar, M. A., &Moghadam, A. S. (2007, June). An efficient method for optimum combination of modes required for pushover analysis. In Proceedings of the ninth Canadian conference on earthquake engineering.
- [17]. ATC-40.: Seismic Evaluation and Retrofit of Reinforced Concrete Buildings: Applied Technology Council (1996)
- [18]. Hakim, R. A., Alama, M. S., &Ashour, S. A. (2014). Seismic assessment of RC building according to ATC 40, FEMA 356 and FEMA 440. Arabian Journal for Science and Engineering, 39, 7691-7699.
- [19]. FEMA-440.: Improvement of Nonlinear Static Seismic Analysis Procedures. Federal Emergency Management Agency (2005)
- [20]. Chopra, A. K., &Goel, R. K. (2002). A modal pushover analysis procedure for estimating seismic demands for buildings. Earthquake engineering & structural dynamics, 31(3), 561-582.
- [21]. Eslami, A., &Ronagh, H. R. (2014). Effect of elaborate plastic hinge definition on the pushover analysis of reinforced concrete buildings. The Structural Design of Tall and Special Buildings, 23(4), 254-271.
- [22]. Mohod, M. V. (2015). Pushover analysis of structures with plan irregularity. J MechCivEng, 12(4), 46-55.
- [23]. D'Ambrisi, A., De Stefano, M., &Tanganelli, M. (2009). Use of pushover analysis for predicting seismic response of irregular buildings: a case study. Journal of Earthquake Engineering, 13(8), 1089-1100.
- [24]. Hakim, R. A. (2013, August). Seismic assessment of RC building using pushover analysis. In International Conference on Engineering and Technology Development (ICETD).
- [25]. Miao, Z., Ye, L., Guan, H., & Lu, X. (2011). Evaluation of modal and traditional pushover analyses in frame-shear-wall structures. Advances in Structural Engineering, 14(5), 815-836.