

Coal Vision Bot for Real-Time Monitoring and Hazardous Detection

Prof. S. A. Sonone¹, Vedant G. Tawlare², Sanket M. Chaurpagar³, Tejas D. Kapankar⁴,
Gayatri P. Bhatkar⁵, Himanshu S. Tumare⁶, Gaurav M. Chaoudhary⁷, Dattaraj D. Sagane⁸

¹Lecturer, Dr. Rajendra Gode Institute of Technology and Research (Polytechnic), Amravati, Maharashtra, India

²⁻⁸Students, Dr. Rajendra Gode Institute of Technology and Research (Polytechnic), Amravati, Maharashtra,

Abstract: *The rapid growth of industries, mining operations, and hazardous working environments has increased the demand for intelligent systems capable of ensuring both safety and operational efficiency. Traditional monitoring methods often fail to provide comprehensive, real-time insights, leaving critical gaps in hazard prevention and emergency response. This paper presents an advanced coal vision bot designed for real-time monitoring and hazardous detection. The system integrates intelligent sensing mechanisms to continuously observe environmental conditions, detect ground vibrations, and identify hazardous activities. It operates efficiently in diverse conditions, including low-light environments, ensuring round-the-clock surveillance. The early warning capability of the system enhances worker safety and reduces accident risks. This research highlights the importance of automation and smart monitoring systems in modern industrial and mining environments.*

Keywords: hazardous working environments.

I. INTRODUCTION

Coal mining and industrial environments are inherently hazardous due to the presence of toxic gases, unstable ground conditions, and limited visibility. Traditional monitoring systems rely heavily on manual inspections, which are often inefficient and prone to human error.

With the advancement of robotics, embedded systems, and intelligent monitoring technologies, there is a growing need for automated solutions. The Coal Vision Bot is designed to provide real-time monitoring, detect hazardous conditions, and enhance safety in mining and industrial environments.

II. OBJECTIVES

- To design a robotic system for real-time monitoring in coal mines
- To detect hazardous conditions such as gas leakage, vibrations, and abnormal activities
- To provide continuous surveillance in day and night conditions
- To improve worker safety and reduce accident risks
- To enable early warning and quick response mechanisms

III. LITERATURE REVIEW

- Existing safety systems in mining industries include:
- Manual inspection methods (time-consuming and risky)
- Fixed sensor-based monitoring systems (limited coverage)
- CCTV surveillance systems (lack environmental sensing)

Recent research emphasizes the use of robotics and IoT for intelligent monitoring. However, many existing systems lack mobility, adaptability, and integrated hazard detection features. The proposed Coal Vision Bot addresses these limitations.



IV. SYSTEM ARCHITECTURE

4.1 Components

- Microcontroller (Arduino/ESP32/Raspberry Pi)
- Gas sensors (for methane, CO, etc.)
- Vibration sensors
- Temperature and humidity sensors
- Camera module (night vision capability)
- Wireless communication module (Wi-Fi/Zigbee)
- Motor driver and robotic chassis
- Power supply (battery system)

4.2 Working Principle

The Coal Vision Bot navigates through mining or industrial areas while continuously collecting environmental data using sensors. The camera module provides live video streaming, while sensors detect hazardous conditions. Data is transmitted wirelessly to a monitoring system where alerts are generated if abnormal conditions are detected.

V. KEY FEATURES

5.1 Real-Time Monitoring

The bot continuously monitors environmental parameters and transmits data instantly to operators.

5.2 Hazardous Gas Detection

Detects gases like methane and carbon monoxide, which are common in coal mines and pose serious risks.

5.3 Vibration Detection

Monitors ground vibrations to identify potential cave-ins or structural instability.

5.4 Night Vision Surveillance

Equipped with cameras that function effectively in low-light or dark environments.

5.5 Wireless Communication

Allows remote monitoring and control, ensuring safety without requiring human presence in hazardous zones.

VI. METHODOLOGY

- Design of robotic structure
- Integration of sensors and camera modules
- Development of control algorithms
- Implementation of wireless communication system
- Testing in simulated hazardous environments

VII. ADVANTAGES

- Enhances worker safety
- Provides early hazard detection
- Reduces need for human presence in dangerous areas
- Enables continuous monitoring
- Improves emergency response time



VIII. APPLICATIONS

- Coal mining industries
- Underground tunnels
- Industrial plants
- Hazardous chemical environments
- Disaster management operations

IX. LIMITATIONS

- Limited battery life
- Signal loss in deep underground environments
- Initial deployment cost
- Requires maintenance in harsh conditions

X. FUTURE SCOPE

- Integration with Artificial Intelligence for predictive analysis
- GPS and autonomous navigation system
- Cloud-based data storage and analytics
- Integration with alarm and evacuation systems
- Use of drones for extended monitoring

XI. CONCLUSION

The Coal Vision Bot represents a significant step toward improving safety and efficiency in hazardous environments such as coal mines. By combining real-time monitoring, intelligent sensing, and wireless communication, the system provides an effective solution for early hazard detection. It reduces risks to human workers and enhances operational efficiency. With future advancements, such systems can become an essential part of smart industrial safety infrastructure.

REFERENCES

- [1]. Safety in Coal Mines – International Mining Journals
- [2]. IoT-Based Monitoring Systems – IEEE Publications
- [3]. Robotics in Hazardous Environments – Springer
- [4]. Industrial Safety Systems – Elsevier

