IJARSCT
International Journal of Advanced Research in Science, Communication and Technology
International Open-Access, Double-Blind, Peer-Reviewed, Refereed, Multidisciplinary Online Journal
ISSN: 2581-9429
Volume 6, Issue 1, November 2026
Impact Factor: 8.2

IoT Based Smart Railway Track Crack Detection System Project Report

Mr. Gawali S. B., Mr. Salunke V. G., Mr. Kolekar S. G., Prof. Kosgiker G. M
Department of Electronics and Telecommunication Engineering
Brahmdevdada Mane Institute of Technology, Solapur

Abstract : *Railway transportation is an important mode of transport for passengers and goods. Railway track safety is essential for safe and reliable operations. Cracks, fractures, and other defects may cause accidents, infrastructure damage, and loss of human life. Traditional inspection mainly depends on manual checking and periodic inspection, which can require considerable time and human effort. An automated monitoring approach can demonstrate an improved method of railway track inspection.*

The IoT Based Smart Railway Track Crack Detection System is a prototype for automatic railway track monitoring using embedded systems and Internet of Things (IoT) technology. An ESP32 microcontroller acts as the main control unit. The sensor monitors predefined gaps or abnormal conditions on a model railway track. A GPS module provides geographical location information, an L298N motor driver controls the DC motor, and a buzzer generates an alert when an abnormal condition is detected. The ESP32 can transmit available monitoring information through Wi-Fi to an IoT-based dashboard.

The main objective is to reduce the effort involved in manual inspection and demonstrate a smart, low-cost, automated railway track monitoring prototype combining sensor-based detection, GPS location information, motor control, and wireless communication.

The prototype demonstrates the potential use of embedded systems and IoT in railway safety applications. Further improvements may include advanced crack-detection sensors, cameras, artificial intelligence, and reliable communication systems. Actual structural rail-crack detection requires appropriate sensing technology and experimental validation before real railway use.

Key Words: Iot based smart railway track crack detection system

I. INTRODUCTION

Railway safety is an important concern due to increasing train numbers, continuous heavy loads, and the risk of accidents caused by track defects. Traditional inspection depends on manual checking and specialized equipment. Manual inspection can be time-consuming, and newly developed defects may not be identified immediately. Embedded systems, Internet of Things (IoT) technology, and wireless communication provide the opportunity to develop smart railway monitoring solutions.

The proposed system combines sensor-based defect detection with real-time fault indication and remote monitoring. A crack-detection sensor monitors the track surface for predefined discontinuities or abnormal conditions. The ESP32 processes the sensor signals; when a defined fault condition is detected, it activates a buzzer. The inspection trolley can move along a model railway track while the sensor monitors the selected area.

When a suspected crack or track discontinuity is detected, the system can transmit fault status to a web-based dashboard through Wi-Fi. A GPS module can provide geographical coordinates when a valid satellite signal is available, helping identify the area that needs further inspection. The ESP32 coordinates sensor readings, buzzer

IJARSCT
International Journal of Advanced Research in Science, Communication and Technology
International Open-Access, Double-Blind, Peer-Reviewed, Refereed, Multidisciplinary Online Journal
ISSN: 2581-9429
Volume 6, Issue 1, November 2026
Impact Factor: 8.2

operation, motor control, and wireless communication. The prototype can be programmed using the Arduino IDE and tested for detection performance, response time, false alarms, and communication reliability.

The project aims to provide a simple and cost-effective prototype for detecting predefined track-surface defects and reporting suspected faults. Further development may include camera-based inspection, advanced ultrasonic sensing, cloud monitoring, automatic fault mapping, and machine-learning-based classification. Structural rail-crack detection requires suitable sensors and validation before real railway application.

II. PROBLEM STATEMENT

Conventional railway track inspection mainly depends on manual checking and specialized inspection equipment. These methods may be time-consuming, and identification of newly developed defects may be delayed. There is therefore a need for improved monitoring that supports defect detection, timely fault reporting, and convenient observation of track conditions.

A sensor-based system can identify predefined track-surface discontinuities or abnormal conditions and generate an alert. However, sensor placement, environmental conditions, and the sensing technology selected can affect readings. A basic sensor may fail to identify a particular defect or may generate false alarms.

The proposed system uses an ESP32 to process sensor signals, control the buzzer, and manage wireless communication. During monitoring, the inspection trolley moves along a model track. When a predefined abnormal condition is detected, the buzzer is activated and the fault status can be sent to a web dashboard. An optional GPS module can record the location when satellite reception is available.

The project addresses delays and limitations in conventional inspection and the lack of continuous automated fault reporting in a basic monitoring system. It aims to provide a low-cost prototype that can be tested using intact track sections and predefined discontinuities to evaluate detection performance, response time, false alarms, and communication reliability.

II. LITERATURE REVIEW

The literature review considers railway track crack detection, railway safety monitoring, sensor-based inspection, and IoT-based fault reporting. Research prototypes have used infrared and ultrasonic sensors, microcontrollers, GPS modules, wireless communication, and alert circuits to monitor track conditions.

Sensor-Based Railway Track Detection

Sensor-based systems identify predefined abnormalities or changes in railway track surfaces. A sensor sends signals to a microcontroller for processing, and an alert is generated when a predefined fault condition is detected. Performance can be affected by sensor position, environmental conditions, and the type of defect.

Infrared Sensor-Based Monitoring

Infrared (IR) sensors have been explored for detecting track discontinuities and surface abnormalities. They monitor the track and provide an output when a change is detected. IR sensors are simple and economical, but their performance can be affected by surface reflectivity, ambient light, alignment, and distance. An IR sensor alone cannot reliably identify every type of structural crack inside a railway rail.

Microcontroller and IoT-Based Monitoring

Microcontrollers such as Arduino, ESP8266, and ESP32 process sensor inputs and control buzzers, motors, and indicators. The ESP32 is useful for IoT applications because built-in Wi-Fi can transmit fault information to a remote platform. IoT connectivity can display suspected fault conditions on a web dashboard, but effectiveness depends on network availability, communication reliability, and accurate sensor data.

GPS-Based Fault Location

A GPS receiver can provide coordinates associated with a suspected defect. These coordinates can be included in a fault record and displayed on a monitoring platform. GPS performance depends on satellite availability and reception conditions, and the location reading must be associated with the correct detection event.

IJARSCT
International Journal of Advanced Research in Science, Communication and Technology
International Open-Access, Double-Blind, Peer-Reviewed, Refereed, Multidisciplinary Online Journal
ISSN: 2581-9429
Volume 6, Issue 1, November 2026
Impact Factor: 8.2

Research Gap

Sensor-based detection, microcontroller control, IoT communication, and GPS each support railway monitoring. A basic system may not combine local fault indication, wireless reporting, and location information in one prototype. Simple sensors may also be unable to detect every structural rail crack. The proposed project integrates a crack-detection sensor, ESP32, buzzer, Wi-Fi dashboard, and optional GPS module. Practical testing is required to evaluate detection, response time, false alarms, and communication reliability.

III. OBJECTIVES

Develop a smart, cost-effective railway track monitoring prototype that detects suspected track defects using sensor technology and IoT communication.

Implement sensor-based detection of predefined abnormalities on the railway track surface. The ESP32 processes sensor output and determines whether the programmed detection condition is satisfied.

Provide an immediate fault-alert mechanism. When a suspected defect is detected, the microcontroller activates a buzzer to notify the operator that the track section requires further inspection.

Integrate the ESP32 with the crack-detection sensor, buzzer, Wi-Fi communication, optional GPS module, and DC motor with motor driver for monitoring, reporting, and movement of the inspection trolley.

Provide a web-based dashboard to view fault status and, when implemented, detection time and GPS coordinates. Study detection rate, false alarm rate, response time, and wireless communication reliability under controlled model-track conditions.

Create a foundation for future improvements such as advanced ultrasonic sensing, camera-based detection, image processing, cloud storage, automatic fault mapping, and machine-learning-based classification.

IV. BLOCK DIAGRAM




Fig. 4.1: Block Diagram of IoT Based Smart Railway Track Crack Detection System

V. WORKING

The system demonstrates automatic railway track monitoring using an ESP32 microcontroller, crack-detection sensor, buzzer, Wi-Fi connectivity, web-based dashboard, power supply, and optional GPS module. A DC motor and motor driver can move the inspection trolley along a model railway track.

IJARSCT
International Journal of Advanced Research in Science, Communication and Technology
International Open-Access, Double-Blind, Peer-Reviewed, Refereed, Multidisciplinary Online Journal
ISSN: 2581-9429 Volume 6, Issue 1, November 2026 Impact Factor: 8.2

System Initialization and Wi-Fi Connection

When the power supply is switched ON, the ESP32 executes the program uploaded through the Arduino IDE and initializes the sensor, buzzer, and communication interface. It attempts to connect to an available Wi-Fi router or mobile hotspot. Once connected, it is ready to transmit monitoring information. Local sensor monitoring and buzzer operation can continue when Wi-Fi is unavailable, depending on the program.

Track Monitoring and Crack Detection

The crack-detection sensor monitors the selected area as the trolley moves along the model track. Depending on the hardware configuration, an infrared (IR) sensor or another suitable sensing method can be used. The sensor provides signals according to the surface condition. When a gap, discontinuity, or predefined abnormal condition is introduced, the ESP32 compares the sensor output with the programmed detection condition and identifies a suspected defect. Detection depends on sensor type, position, calibration, and defect characteristics. A basic IR sensor does not reliably detect every real railway rail crack.

Fault Alert Generation

Under normal conditions, the buzzer remains OFF. When the sensor indicates a predefined abnormal condition, the ESP32 activates the buzzer to provide an audible warning. The buzzer can be switched OFF when the sensor returns to the normal state, according to the program. The alert indicates a suspected abnormality; it does not confirm the presence or severity of a rail crack.

GPS Location and IoT Dashboard

When a GPS module receives a valid satellite signal, it provides coordinates that the ESP32 can associate with a detected fault. GPS reception may be limited in tunnels, covered areas, or locations with poor satellite visibility. Through Wi-Fi, the ESP32 can send fault status to a configured web dashboard or IoT platform. The dashboard may display track status, fault alert, detection time, and GPS coordinates when implemented. Dashboard operation depends on the selected platform, network availability, and correct program configuration.

Trolley Movement and System Response

The ESP32 sends control signals to the L298N motor driver, which supplies the required current from an appropriate power source and controls the DC motor. As the trolley moves, the sensor monitors different track sections. When an abnormality is detected, the system activates the buzzer and prepares a fault notification; if automatic stopping is programmed, the trolley can also stop. Testing should cover normal and simulated fault conditions, buzzer response, dashboard updates, and wireless reliability. The prototype is for academic demonstration and is not a certified railway safety device.


VI. HARDWARE COMPONENTS

COMPONENT	SPECIFICATION AND FUNCTION
1. ESP32 Development Board	ESP32-WROOM-32; 3.3 V logic; typically 5 V through USB or VIN; Wi-Fi 2.4 GHz and Bluetooth. Main controller that processes sensor data, controls the buzzer and motor driver, and sends monitoring data to the IoT dashboard.
2. Ultrasonic Sensor (HC-SR04)	Operating voltage: 5 V; measuring range: approximately 2 cm to 400 cm; Trigger and Echo digital signals. Measures distance to the track surface; distance changes can indicate possible gaps or irregularities on the model track.
3. GPS Module (NEO-6M)	Input depends on breakout board, commonly 3.3–5 V; UART serial communication. Receives satellite signals and provides latitude and longitude for a railway-track abnormality alert when a valid fix is available.
4. Motor Driver (L298N)	Dual H-bridge module; logic supply typically 5 V; motor supply depends on motor requirements. Interfaces the ESP32 with the DC motor and controls motor direction and speed.

IJARSCT
International Journal of Advanced Research in Science, Communication and Technology
International Open-Access, Double-Blind, Peer-Reviewed, Refereed, Multidisciplinary Online Journal
ISSN: 2581-9429
Volume 6, Issue 1, November 2026
Impact Factor: 8.2

COMPONENT	SPECIFICATION AND FUNCTION
5. DC Motor	Low-voltage DC geared motor; commonly 3–12 V depending on specifications. Moves the inspection prototype along the model railway track so the sensor can monitor different sections.
6. Buzzer	Active electronic buzzer; commonly 3.3–5 V depending on model. Produces an audible warning when the ESP32 detects an abnormal distance or possible gap.
7. Breadboard	Solderless prototyping board with internally interconnected contact strips. Provides connections for circuit testing and modification without soldering.
8. Connecting Wires	Male-to-male, male-to-female, and female-to-female jumper wires with copper conductors and insulation. Establish electrical connections among the ESP32, sensor, GPS, motor driver, and buzzer.
9. Power Supply / Battery	USB supply and external DC battery or power source. Supplies the required voltage to the ESP32, sensors, and motor driver; a separate suitable supply is used for the DC motor.
10. Railway Track Model	Miniature railway track prototype. Represents the track and provides a test surface where gaps or irregularities can be introduced for demonstration.
11. IoT Web Dashboard	Web-based platform such as Blynk or ThingSpeak, connected through Wi-Fi/Internet. Displays monitoring status, sensor information, and available GPS coordinates for remote viewing.

AIN COMPONENTS - IMAGE GALLERY




ESP32 Development Board



Ultrasonic Sensor (HC-SR04)



GPS Module (NEO-6M)



Motor Driver (L298N)




DC Geared Motor



Buzzer

IJARSCT
International Journal of Advanced Research in Science, Communication and Technology
International Open-Access, Double-Blind, Peer-Reviewed, Refereed, Multidisciplinary Online Journal
ISSN: 2581-9429 Volume 6, Issue 1, November 2026 Impact Factor: 8.2




Breadboard



Connecting Jumper Wires



Power Supply / Battery




Railway Track Model



IoT Web Dashboard

VII. CIRCUIT DIAGRAM



* ECHO through a 1 kΩ / 2 kΩ divider (5 V → 3.3 V). All modules share a common GND.

Fig. 5.1: Circuit Diagram

Complete Working Process of the Project

1. Power ON: The power supply provides power to the ESP32, sensors, and motor driver.
2. System initialization: ESP32 initializes the ultrasonic sensor, GPS module, buzzer, motor driver, and Wi-Fi.
3. Prototype movement: ESP32 sends signals to the L298N motor driver, which operates the DC motor.
4. Track monitoring: The ultrasonic sensor measures the distance between itself and the railway track surface.
5. Abnormality detection: ESP32 compares the measured distance with a predefined threshold and identifies a

IJARSCT
International Journal of Advanced Research in Science, Communication and Technology
International Open-Access, Double-Blind, Peer-Reviewed, Refereed, Multidisciplinary Online Journal
ISSN: 2581-9429
Volume 6, Issue 1, November 2026
Impact Factor: 8.2

possible gap or irregularity.

6. Buzzer alert: The buzzer turns ON and generates a warning sound.
7. GPS location: The GPS module provides latitude and longitude when satellite reception is available.
8. IoT monitoring: ESP32 sends abnormality status and available GPS information to the web dashboard using Wi-Fi.

VIII. ADVANTAGES AND APPLICATIONS

1. ADVANTAGES	2. APPLICATIONS
Automatic Crack Detection: Identifies predefined cracks, gaps, or abnormal changes on the railway track model and reduces continuous manual observation.	Railway Track Inspection: Prototype for automated inspection and collection of sensor information.
Real-Time Track Monitoring: The robot moves along the track and the sensor sends information to the ESP32.	Railway Crack and Gap Detection: Demonstrates detection of predefined gaps or changes in track arrangement.
GPS-Based Location Tracking: NEO-6M provides latitude and longitude to identify the approximate location of a reported fault.	Railway Safety Monitoring: Alerts indicate abnormal conditions that need further inspection.
IoT-Based Communication: ESP32 Wi-Fi sends available information to a dashboard for remote viewing.	GPS-Based Fault Identification: Location information helps identify the approximate area of a reported fault.
Instant Audio Alert: The buzzer provides an immediate sound indication when a predefined fault is detected.	Remote Railway Monitoring: Wi-Fi transmits sensor information to a web-based dashboard.
Reduction in Manual Inspection: Demonstrates an automated approach to repetitive inspection.	Railway Maintenance Support: Information can help identify track sections requiring additional checking and repair.
Low-Cost System: Uses affordable components and is suitable for educational prototyping.	Robotic Inspection Systems: Demonstrates mobile robots for infrastructure and industrial monitoring.
Portable and Compact Design: A small robotic vehicle moves along a miniature railway track.	Railway Research and Development: Useful for studying sensors, embedded systems, robotics, and IoT communication.
Easy Maintenance and Modification: Modular components can be tested, replaced, or upgraded.	Educational Demonstration: Suitable for engineering exhibitions, laboratory experiments, and technical demonstrations.
Improved Safety Support: Early identification of possible abnormalities can help maintenance teams decide where further inspection is needed.	Industrial Automation: The basic fault-detection concept can be adapted to other surfaces and mechanical structures.
Continuous Sensor Data Collection: ESP32 receives readings during robot movement for observation and analysis.	Remote Alert Systems: Buzzer and dashboard provide local and remote indications, depending on implementation.
Multiple Component Integration: Combines sensors, GPS, motor control, wireless communication, and an alarm system.	Smart Transportation Infrastructure: Demonstrates IoT and embedded technology for intelligent transportation.

IJARSCT
International Journal of Advanced Research in Science, Communication and Technology
International Open-Access, Double-Blind, Peer-Reviewed, Refereed, Multidisciplinary Online Journal
ISSN: 2581-9429
Volume 6, Issue 1, November 2026
Impact Factor: 8.2

IX. FUTURE SCOPE

- **Artificial Intelligence Integration**: AI and machine-learning algorithms can analyze sensor readings and images to improve fault classification.
- **Camera-Based Crack Detection:** A high-resolution camera can capture track images for image-processing-based identification of visible cracks and surface damage.
- **Advanced Sensor Integration:** High-precision optical, ultrasonic, laser, and vibration sensors can improve detection of different track abnormalities.
- **GSM Module Integration:** A GSM module can send SMS notifications to maintenance staff when a fault is detected, including where Wi-Fi is unavailable.
- **Mobile Application Development:** An Android application can display sensor readings, GPS coordinates, fault alerts, and inspection status.
- **Cloud-Based Data Storage:** ThingSpeak or Firebase can store inspection data for performance analysis and maintenance planning.
- **Improved GPS Accuracy:** An advanced GPS receiver or RTK-GNSS can improve the location accuracy under suitable conditions.
- **Solar-Powered System:** Solar panels can provide supplementary power and reduce dependence on frequent battery charging.
- **Automatic Fault Classification:** Suitable sensors and algorithms can classify surface cracks, gaps, track misalignment, and damaged sections.
- **Automatic Emergency Notification:** An advanced alert mechanism can notify the responsible maintenance team when a serious abnormality is detected.
- **Improved Robot Design:** A stronger chassis, better wheels, improved suspension, and efficient motors can provide more stable movement.
- **Wireless Data Transmission:** Advanced wireless technologies can improve data transfer between the inspection robot and monitoring station.
- **Predictive Maintenance:** Historical inspection data and machine learning could identify recurring abnormalities and predict maintenance requirements.
- **Automatic Inspection Reports:** Reports can include fault details, GPS coordinates, date, time, and sensor readings.
- **Integration with Railway Control Systems:** Integration may be considered after proper testing, certification, and safety validation.

X. CONCLUSION

The IoT Based Smart Railway Track Crack Detection System demonstrates an automated approach to railway track inspection and monitoring. Its objective is to identify possible cracks, gaps, and abnormal conditions on railway tracks and provide timely alerts to support railway safety. The system combines embedded technology, sensors, robotics, GPS, and IoT communication.

The ESP32 development board acts as the main controller and processes information received from the sensors. The IR sensor helps detect predefined cracks or gaps in the railway track model, while the HC-SR04 ultrasonic sensor measures the distance of nearby objects. The NEO-6M GPS module provides geographical location information, and the L298N motor driver controls the DC gear motors to move the inspection robot.

When an abnormal condition is detected, the ESP32 activates the active buzzer to generate an audio warning. Built-in Wi-Fi connectivity can transmit monitoring information to an IoT dashboard, allowing the user to observe available information remotely.

IJARSCT
International Journal of Advanced Research in Science, Communication and Technology
International Open-Access, Double-Blind, Peer-Reviewed, Refereed, Multidisciplinary Online Journal
ISSN: 2581-9429
Volume 6, Issue 1, November 2026
Impact Factor: 8.2

The project demonstrates how automation can reduce repetitive manual inspection effort and help identify possible track problems at an early stage. It provides practical knowledge of microcontrollers, sensor interfacing, motor control, GPS communication, and IoT-based monitoring. The affordable components make it suitable for academic projects, exhibitions, and prototype development.

The model can be improved through artificial intelligence, machine learning, high-resolution cameras, advanced crack-detection sensors, GSM communication, cloud storage, and mobile applications. Further testing and validation are required before any real railway application. The project highlights the importance of embedded systems and IoT in developing intelligent railway monitoring solutions.

REFERENCES

1. S. Wattal, S. K. Spear, M. H. Imtiaz and E. Sazonov, "A polypyrrole-coated textile electrode and connector for wearable ECG monitoring," 2018 IEEE 15th International Conference on Wearable and Implantable Body Sensor Networks (BSN), Las Vegas, NV, USA, 2018, pp. 54–57, doi: 10.1109/BSN.2018.8329657.
2. W. Liu, C. Li and J. Zhang, "Design of real-time ECG monitoring wearable equipment based on the Holter system," 2022 4th International Academic Exchange Conference on Science and Technology Innovation (IAECST), Guangzhou, China, 2022, pp. 1585–1588, doi: 10.1109/IAECST57965.2022.10062266.
3. W. Tong, C. Kan and H. Yang, "Sensitivity analysis of wearable textiles for ECG sensing," 2018 IEEE EMBS International Conference on Biomedical & Health Informatics (BHI), Las Vegas, NV, USA, 2018, pp. 157–160, doi: 10.1109/BHI.2018.8333393.
4. H. Ozkan, O. Ozhan, Y. Karadana, M. Gulcu, S. Macit and F. Husain, "A Portable Wearable Tele-ECG Monitoring System," IEEE Transactions on Instrumentation and Measurement, vol. 69, no. 1, pp. 173–182, 2020, doi: 10.1109/TIM.2019.2895484.
5. T. Shaown, I. Hasan, M. M. R. Mim and M. S. Hossain, "IoT-based Portable ECG Monitoring System for Smart Healthcare," 2019 1st International Conference on Advances in Science, Engineering and Robotics Technology (ICASERT), Dhaka, Bangladesh, 2019, pp. 1–5, doi: 10.1109/ICASERT.2019.8934622.
6. Z. Yang, Q. Zhou, L. Lei, K. Zheng and W. Xiang, "An IoT-cloud Based Wearable ECG Monitoring System for Smart Healthcare," Journal of Medical Systems, vol. 40, no. 12, Article 286, 2016, doi: 10.1007/s10916-016-0644-9.
7. M. L. Sahu, M. Atulkar, M. K. Ahirwal and A. Ahamad, "IoT-enabled cloud-based real-time remote ECG monitoring system," Journal of Medical Engineering & Technology, vol. 45, no. 6, pp. 473–485, 2021, doi: 10.1080/03091902.2021.1921870.