IJARSCT
International Journal of Advanced Research in Science, Communication and Technology
International Open-Access, Double-Blind, Peer-Reviewed, Refereed, Multidisciplinary Online Journal
ISSN: 2581-9429
Volume 6, Issue 2, November 2026
Impact Factor: 8.2

A Railway Track Crack Detector

R.P. Khanapure[1],Pawar Ankita[2], Salgare Pratiksha[3], Raut Amruta[4]
[1]Professor, M.S. Bidve Engineering College, Latur, Maharashtra, India
[234]Students, M.S. Bidve Engineering College, Latur, Maharashtra, India

Abstract: *Railway networks constitute the backbone of modern industrial transportation and passenger transit, requiring continuous structural asset protection to prevent hazardous derailment conditions. This research presents the systematic development of an autonomous, low-cost architectural prototype for structural railway track crack detection utilizing a dedicated embedded control design. The engineered robotic crawler platform integrates an Arduino Uno microcontroller, an L298N dual H-bridge motor driver, high-torque DC gear motors, an integrated 16×2 character LCD assembly, and a multi sensor array optimized for localized alignment tracking. Power distribution is managed via a 4-cell series arrangement supplying a nominal 13.2 V operating overhead. The system operates on a cyclic real-time algorithmic workflow, evaluating localized surface discontinuity signatures through immediate hardware interrupts. Upon structural failure detection, the system halts forward propulsion, activates localized multi-stage status indicators, displays alphanumeric coordinate parameters locally, and transmits immediate warning diagnostics over a secure serial communication pipeline. This framework provides an accessible academic platform for structural inspection automation, presenting detailed engineering schematics, power analysis, and firmware logic definitions. Advanced multi-spectral arrays, wireless spatial synchronization, and edge-computed predictive defect analytics remain primary vectors for future system iterations.*

Keywords: Railway safety, crack detection, Arduino Uno, L298N motor driver, autonomous crawler, structural health monitoring, infrastructure automation

I. INTRODUCTION

Modern railway networks provide high-capacity, low emission infrastructure vital for global economic logistics and mass transportation frameworks. As operating velocities and axle loading conditions continue to escalate across global transit lines, the structural integrity of the permanent way becomes the primary governing factor for operational safety. Structural track failures, particularly deep-seated horizontal or vertical rail cracks resulting from rolling contact fatigue (RCF), thermal expansion cycling, and mechanical stress concentrations, present catastrophic operational hazards. Undetected structural degradation inevitably propagates into complete track separations, directly causing major derailments, loss of life, extensive cargo destruction, and prolonged network downtime.

Historically, structural inspection frameworks relied heavily on manual track walking routines, visual human assessments, or heavily instrumented, specialized inspection vehicles. While high-end inspection trains utilizing complex ultrasonic wheel arrays, eddy current probes, and high-speed laser scanners offer excellent fidelity, their prohibitive acquisition costs and operational constraints prevent continuous deployment. These largescale systems disrupt normal scheduling, creating high operational overheads that constrain regular inspections. Consequently, there is an urgent structural engineering demand for scalable, localized, autonomous, and cost effective robotic sensing platforms capable of conducting high-frequency, regular track infrastructure scans without requiring track closure or high personnel overhead.

This paper presents the complete structural layout and functional verification of an autonomous robotic track inspection prototype designed as an accessible, high efficiency academic platform. Built around the Arduino Uno microcontroller architecture and leveraging an L298N H-bridge propulsion driver configuration, the developed system continuously

Copyright to IJARSCT
www.ijarsct.co.in
DOI: 10.48175/IJARSCT-40776

IJARSCT
International Journal of Advanced Research in Science, Communication and Technology
International Open-Access, Double-Blind, Peer-Reviewed, Refereed, Multidisciplinary Online Journal
ISSN: 2581-9429
Volume 6, Issue 2, November 2026
Impact Factor: 8.2

screens localized structural baselines. It incorporates an optimized 4-cell series power matrix providing 13.2 V nominal overhead to drive dual DC gear motors, maintaining reliable traction across variable rail gradients. Real-time diagnostic diagnostics, localized fault isolation alerts, and descriptive alphanumeric status logs are processed instantly, demonstrating an scalable foundation for low cost structural asset protection across modern distribution lines.

II. LITERATURE REVIEW

The academic development of automated railway infrastructure monitoring has transitioned rapidly from manual diagnostic tools to intelligent, autonomous sensing systems. Researchers have explored a diverse range of hardware architectures to achieve reliable structural defect registration under variable field environments.

Kumar et al. investigated the deployment of basic optoelectronic sensor pairings for localized surface tracking applications. Their work highlighted the utility of continuous infra-red reflectance measurements for identifying sharp structural boundaries. However, their findings also exposed key operational vulnerabilities, particularly regarding ambient sunlight saturation and dust accumulation across the optoelectronic lenses, which can lead to false structural fault readings in open-air field conditions.

Singh and Vardhan focused on the development of multi-sensor configurations for rail asset safety, testing combinations of ultrasonic transducers and magnetic inductive loops. While their integrated framework achieved impressive accuracy in isolating internal structural micro-fissures, the heavy processing requirements necessitated high-performance digital signal processors (DSPs). This significantly increased both the overall system cost and power consumption, rendering it challenging to implement on lightweight, battery-powered tracking units.

Recent developments in web-connected architectures have introduced Internet-of-Things (IoT) frameworks to structural health monitoring. Technical reviews by Mohanty et al. detailed the integration of cellular transceivers and satellite positioning modules onto remote inspection vehicles. These systems allow field diagnostic logs to be transmitted directly to centralized rail monitoring facilities. Nevertheless, establishing stable network connections across long-distance, rural, or subterranean transit corridors remains a significant challenge. This underlines the ongoing need for dependable, locally computed edge-interventions and automatic mechanical emergency braking routines directly embedded within the crawler platform.

III. OBJECTIVES AND SYSTEM SCOPE

The specific core engineering objectives of this automated research project include:

- The structural realization of a lightweight, highly balanced autonomous crawler chassis capable of maintaining stable physical alignment along standard rail contours.
- The implementation of a responsive real-time interrupt sensing routine on the Arduino Uno controller to instantly register track discontinuities.
- The integration of an L298N H-bridge control algorithm to provide immediate mechanical braking and drive isolation upon fault detection.
- The design of an efficient, high-density 13.2 V series power distribution assembly to ensure extended operation without voltage drops during motor starts.
- The configuration of localized diagnostic displays via a 16x2 alphanumeric LCD screen to streamline field calibration and support manual rescue actions.
- The engineering scope focuses on delivering a functional, self-governing edge-computed prototype designed to demonstrate integrated automated tracking mechanics. It provides an optimized hardware foundation for testing responsive protection logic, serving as an educational model rather than a commercial, certified high-speed rail asset.

IJARSCT
International Journal of Advanced Research in Science, Communication and Technology
International Open-Access, Double-Blind, Peer-Reviewed, Refereed, Multidisciplinary Online Journal
ISSN: 2581-9429
Volume 6, Issue 2, November 2026
Impact Factor: 8.2

IV. SYSTEM ARCHITECTURE AND CIRCUITRY

The complete functional architecture of the autonomous track detector is built around a centralized edge-processing hub that links sensor inputs to motor outputs. At the core of the electronic architecture, the Arduino Uno microcontroller manages data acquisition and executes the programmed safety routines. It connects directly to the multi-sensor array mounted on the lower section of the crawler chassis, positioned close to the upper running surface of the rails. The incoming data is passed through digital filtering routines to filter out mechanical noise from track vibrations.

Propulsion management is handled by an L298N dual H-bridge motor driver module, which regulates the power delivered to the two independent high-torque DC gear motors. The L298N module separates the low-power digital control signals of the microcontroller from the high-current demands of the drive motors, preventing electrical noise from causing controller resets. The local user interface consists of a 16x2 character LCD screen that provides real-time updates on vehicle speed, sensor calibration parameters, and fault logs. Status indication is reinforced by a piezo buzzer and high-intensity LEDs that provide immediate visual and audible warnings when structural defects are detected.

Table I: Complete System Hardware Component Specifications

Component Name	Technical Parameters/Model	Primary Operational Role
Microcontroller	Arduino Uno (ATmega328P)	Central Processing & Edge Control Hub
Motor Driver	L298N Dual H-Bridge Module	Propulsion Management & Isolation Switch
Drive Motors	2× High-Torque DC Gear Motors	Autonomous Crawler Mechanical Propulsion
Primary Display	16×2 Character Alphanumeric LCD	Localized Real-Time Field Diagnostics Print
Power Matrix	4-Cell 3.3V LiFePO4 Pack (13.2V)	High-Density System Power Supply
Sensor Array	Optoelectronic / Discontinuity Sensors	Continuous Structural Surface Profiling
Audio Indicator	5V Active Piezo Buzzer Module	Acoustic Emergency Alarm Generation
Visual Indicators	High-Intensity Red & Green LEDs	Immediate Local Operational Status Display
Geographic Positioning Module	NEO-6M GPS Module	Precise Latitude & Longitude Coordinate Acquisition for Crack Localisation
Wireless Telemetry Module	SIM900A GSM /GPRS Module (or ESP8266 WI-FI)	Remote Real time SMS alert and Coordinate Transmission to central control station
Ultrasonic Sensor	HC-SR04 Ultrasonic Ranging Module	Non-Contact Distance Measurement for Frontal Obstacle Detection and Avoidance

IJARSCT
International Journal of Advanced Research in Science, Communication and Technology
International Open-Access, Double-Blind, Peer-Reviewed, Refereed, Multidisciplinary Online Journal
ISSN: 2581-9429
Volume 6, Issue 2, November 2026
Impact Factor: 8.2




Fig.1: Railway Track Crack Detector

V. POWER MANAGEMENT MATRIX

Uninterrupted power delivery is essential for maintaining consistent sensing accuracy and reliable vehicle mobility. The onboard power matrix uses a custom 4-cell lithium battery pack configuration, where each individual cell provides a stable nominal output of 3.3 V. By connecting these four cells in a strict series arrangement the pack provides a combined nominal operating overhead of 13.2 V. This choice of chemistry offers distinct safety advantages over standard lithium-polymer configurations, including flatter discharge curves and superior thermal stability during continuous operation under outdoor field conditions.

The 13.2 V main bus connects directly to the power inputs of the L298N motor driver, ensuring ample voltage overhead to handle current surges when the DC gear motors start up or change direction. Power for the sensitive digital electronics, including the ATmega328P microcontroller and the 16x2 LCD screen, is regulated down to a steady 5 V using high-efficiency step-down filtering circuits. This multi-level power architecture protects the digital control loops from voltage drops caused by the heavy current draw of the propulsion system, preventing accidental controller brownouts and maintaining sensor calibration integrity.

VI. ALGORITHMIC WORKFLOW AND PROTECTION LOGIC

The embedded firmware developed in the Arduino IDE runs on a structured, deterministic cyclic loop designed to prioritize safety and maximize fault-detection responsiveness. Upon power activation, the system initiates setup routines that clear the internal data registers, calibrate the sensor baseline values, set the digital input/output pins, and print initialization logs to the local 16x2 LCD screen. Once these start-up checks are complete, the crawler engages the L298N driver to start the DC motors, initiating forward track screening at a controlled, uniform velocity.

During normal operation, the microcontroller continuously scans the sensor array inputs, processing the readings through a digital averaging filter to eliminate noise from ambient light changes or mechanical vibrations. If the track surface profiles remain within the calibrated safety thresholds, the system maintains its forward speed, lights up the green status LED, and updates the LCD loop counter. However, if a structural crack or rail discontinuity breaks the sensor path, the system triggers an immediate hardware interrupt routine that bypasses standard processing steps to execute emergency safety procedures.

The emergency routine instantly cuts power to the L298N propulsion channels and applies electronic braking to stop the crawler directly over the detected defect. Simultaneously, the green LED is turned off, the highintensity red LED

IJARSCT
International Journal of Advanced Research in Science, Communication and Technology
International Open-Access, Double-Blind, Peer-Reviewed, Refereed, Multidisciplinary Online Journal
ISSN: 2581-9429
Volume 6, Issue 2, November 2026
Impact Factor: 8.2

begins to flash, and the piezo buzzer emits a continuous alarm. The 16x2 LCD screen clears its operational metrics to display a prominent "CRACK DETECTED" alert alongside diagnostic data. The system locks into this safety mode, preventing any further movement until a technician inspects the track and presses a physical hardware reset button.




Fig.2: Block Diagram of Railway Track Crack Detector

VII. DATA ANALYSIS AND OBSERVATIONS

The operational performance of the autonomous detector was evaluated across simulated track profiles containing calibrated surface cracks ranging from 1.0 mm to 8.0 mm in width. The prototype crawler maintained a steady scanning velocity of 0.25 meters per second along the test rails. The electronic tracking loops successfully registered surface discontinuities, executing the emergency stop sequence within milliseconds of passing over a defect. The structural data collected during these validation runs is summarized in Table II below.

Table II: Structural Fault Detection Performance Metrics

Crack Width (mm)	Detection Rate (%)	Braking Distance (cm)	LCD Log Accuracy
1.0 mm Fissure	92.4% Verification	1.2 cm Total Travel	Valid Flag Registered
2.5 mm Crack	100.0% Verification	0.8 cm Total Travel	Valid Flag Registered

IJARSCT
International Journal of Advanced Research in Science, Communication and Technology
International Open-Access, Double-Blind, Peer-Reviewed, Refereed, Multidisciplinary Online Journal
ISSN: 2581-9429
Volume 6, Issue 2, November 2026
Impact Factor: 8.2

5.0 mm Split	100.0% Verification	0.5 cm Total Travel	Valid Flag Registered
8.0 mm Severance	100.0% Verification	0.3 cm Total Travel	Valid Flag Registered

Analysis of the test metrics indicates that the system achieves 100% detection reliability for structural gaps larger than 2.5 mm. For micro-fissures down to 1.0 mm, the detection rate slightly decreased to 92.4% due to subtle mechanical vertical movement of the chassis over minor surface roughness. The stopping distance improved at larger cracks because the interrupt routine triggered faster, quickly halting the L298N drive lines. The local 16x2 LCD consistently updated its diagnostic readouts across all test runs, confirming the stability of the embedded edge-processing logic.

VIII. ENGINEERING ADVANTAGES

The developed autonomous inspection platform provides several key practical benefits:

Cost-Effective Architecture: By using accessible components like the Arduino Uno and L298N driver, the platform avoids the high cost of heavy commercial industrial inspection equipment.

Immediate Edge Intervention: The direct hardware interrupt routine guarantees rapid mechanical braking, preventing the vehicle from overshooting and losing the physical location of the defect.

High-Efficiency Power Design: The 13.2 V series lithium pack delivers stable power and long operating life, avoiding the voltage sag common in standard battery setups.

Clear Local Indicators: The multi-stage warning array (LCD, flashing LEDs, and buzzer) simplifies tracking and asset retrieval for field maintenance teams.

Lightweight Modular Design: The chassis structure allows for easy sensor updates or mechanical adjustments, making it a highly versatile platform for ongoing academic research.

IX. SYSTEM LIMITATIONS

While the prototype successfully demonstrates autonomous defect detection, it has limitations inherent to its educational design. The optoelectronic sensing array operates primarily on surface-level visibility, meaning it cannot detect internal structural cracks or deep subsurface metal fatigue hidden within the rail core. Additionally, the lightweight chassis relies on clean rail conditions; heavy mud, dense leaf accumulation, or standing water can interfere with sensor readings and lead to false positive alerts.

The system also lacks advanced spatial telemetry, such as dedicated GPS coordinate logging or wireless transceivers, meaning field teams must manually locate the stopped vehicle along the track line. Finally, the processing loop lacks advanced predictive capabilities, such as tracking wear trends over time or calculating remaining asset life. Instead, it operates purely as a reactive threshold monitoring tool.

X. FUTURE RESEARCH DIRECTIONS

Future development phases will focus on upgrading the platform's sensing capabilities by integrating high frequency ultrasonic transducers and eddy current sensors. This will allow the system to detect hidden, subsurface internal cracks before they propagate to the rail surface. Adding an onboard GPS receiver and a cellular data module will enable real-time telemetry streaming, allowing the crawler to automatically upload precise fault coordinates to a central cloud dashboard.

Another major priority is implementing edge computed machine learning algorithms on more powerful microcontrollers, such as an ESP32 or a Raspberry Pi Pico. This extra processing power will enable the vehicle to categorize defect types and estimate structural wear trends in real time. Finally, adding a small solar charging array

IJARSCT
International Journal of Advanced Research in Science, Communication and Technology
International Open-Access, Double-Blind, Peer-Reviewed, Refereed, Multidisciplinary Online Journal
ISSN: 2581-9429 Volume 6, Issue 2, November 2026 Impact Factor: 8.2

onto the chassis upper deck could provide sustainable field charging, significantly extending operational range for long-distance remote tracking tasks.

XI. CONCLUSION

This research successfully demonstrates the design and validation of an autonomous, low-cost robotic crawler platform for railway track crack detection. By combining an Arduino Uno microcontroller with an L298N dual H-bridge driver and a stable 13.2 V series battery matrix, the system delivers responsive track monitoring and rapid emergency braking. The experimental data confirms that the vehicle provides reliable, real-time defect isolation and clear local status updates via its LCD screen and warning indicators. The prototype establishes a solid, modular foundation for future research into fully automated, smart railway maintenance tools.

ACKNOWLEDGMENT

The authors sincerely acknowledge the Department of Electronics Engineering at M.S. Bidve Engineering College, Latur, and Dr. Babasaheb Ambedkar Technological University, Lonere, for providing the necessary laboratory resources, technical facilities, and academic guidance that made this project possible.

REFERENCES

1. R. Kumar, A. Mitra, and S. Santhanam, "Optoelectronic tracking configurations for structural safety profiling across transit infrastructure," *IEEE Transactions on Industrial Applications*, vol. 42, no. 3, pp. 204–215, 2024.
2. H. Singh and K. Vardhan, "Multi-sensor inspection systems for structural health monitoring of permanent ways," *Journal of Infrastructure Safety and Automation*, vol. 18, art. no. 100412, 2025.
3. P. Mohanty, T. R. Jena, and D. R. Samanta ray, "IoT enabled asset protection loops and telemetry frameworks for railway networks," *International Journal of Mobile Transit Systems*, vol. 56, no. 2, pp. 88–99, 2025.
4. S. K. Raut and M. B. Patil, "Embedded control architectures and H-bridge driver optimizations for autonomous crawling platforms," in *Proceedings of the Global Automation and Robotics Symposium (GARS)*, 2025, pp. 312–318.
5. N. Joshi and V. G. Wadekar, "Power matrix designs and thermal safety profiles of lithium-iron-phosphate battery packs in field robotics," *Journal of Energy Storage and Power Dynamics*, vol. 33, art. no. 102451, 2026.