IJARSCT
International Journal of Advanced Research in Science, Communication and Technology
International Open-Access, Double-Blind, Peer-Reviewed, Refereed, Multidisciplinary Online Journal
ISSN: 2581-9429
Volume 6, Issue 3, November 2026
Impact Factor: 8.2

Smart Vehicle Headlighting and Auto Switching with Intensity Control

Radhika G[1], Akshatha K S[2], Soundarya[3], Raja[4], Vinay Kumar[5]
Students, Department of Electrical and Electronics Engineering[1-4]
Associate Professor, Department of Electrical and Electronics Engineering[5]
Rao Bahadur Y. Mahabaleshwarappa Engineering College, Ballari, India

Abstract : *This paper presents a intensity Controlusing Arduino UNO. The Smart Vehicle Head Lighting and Auto Switching with Intensity Control system is designed to improve road safety and provide a comfortable driving experience during night-time driving. In conventional vehicles, drivers manually switch between high-beam and low-beam headlights, which may cause inconvenience and lead to accidents due to improper use of headlights.*

Keywords: Arduino UNO, LDR Sensor, IR Sensor, Automatic Headlight Switching, High Beam, Low Beam, Intensity Control, Road Safety.

I. INTRODUCTION

The development of automobile technology has improved vehicle safety, comfort, and efficiency. However, night-time driving remains a major challenge because of poor visibility and improper use of vehicle headlights. Headlights play an important role in providing clear visibility to drivers during night-time and low-light conditions. In conventional vehicles, drivers manually switch between high-beam and low-beam headlights depending on road and traffic conditions. This requires continuous attention and may cause inconvenience while driving.

The Smart Vehicle Head Lighting and Auto Switching with Intensity Control Using Arduino UNO is designed to overcome these problems by automating the headlight control system. The proposed system uses an Arduino UNO microcontroller to monitor surrounding light conditions and detect vehicles approaching from the opposite direction with the help of sensors.

II. OBJECTIVES

The specific objectives are:

1. **Automatic Headlight Switching:** To automatically switch vehicle headlights between high beam and low beam based on traffic conditions.
2. **Light Detection:** To use an LDR sensor to detect surrounding light intensity and identify day-time and night-time conditions.
3. **Vehicle Detection:** To use an IR sensor to detect approaching vehicles from the opposite direction.
4. **Intensity Control:** To adjust the brightness of headlights according to surrounding light conditions.
5. **Reduce Glare:** To prevent bright headlights from disturbing opposite-side drivers and reduce the risk of accidents.
6. **Improve Road Safety:** To provide better visibility and safer driving during night-time and low-light conditions.
7. **Reduce Driver Effort:** To eliminate the need for manual switching between high-beam and low-beam headlights.
8. **Cost-Effective System:** To develop a simple, economical, and efficient automatic headlight control system using Arduino UNO.

IJARSCT
International Journal of Advanced Research in Science, Communication and Technology
International Open-Access, Double-Blind, Peer-Reviewed, Refereed, Multidisciplinary Online Journal
ISSN: 2581-9429
Volume 6, Issue 3, November 2026
Impact Factor: 8.2

III. SCOPE

This project focuses on designing a low-cost, reliable, and automatic headlight control system using Arduino UNO. It can serve as a basic model for developing advanced smart lighting systems in modern automobiles.

IV. SYSTEM DESCRIPTION

Hardware Requirements :

The following hardware components are used to design and implement the proposed system.

Sl. No. Hardware component Specification / Function

1 Arduino UNO ATmega328P microcontroller, 16 MHz
2 LDR Sensor Detects surrounding light intensity
3 IR Sensor Detects approaching vehicles or objects
4 LED Headlights Provides high-beam and low-beam lighting
5 Resistors 220Ω and 10kΩ for current limiting and sensor circuits
6 Transistor / MOSFET Controls LED headlight switching and intensity
7 Breadboard Used for circuit connections
8 Jumper Wires Used to connect electronic components
9 DC Power Supply Provides required operating voltage
10 Connecting Cables Used for electrical connections

Software Requirements :

The following software tools are required for developing and programming the project.

Sl. No. Software Purpose

1 Arduino IDE Writing and uploading the program
2 Embedded C / C++ Programming the Arduino UNO
3 Arduino USB Driver Communication between computer and Arduino
4 Serial Monitor Monitoring sensor readings and debugging
5 Proteus (optional) Circuit simulation and testing

A. Working Principle

The Smart Vehicle Head Lighting and Auto Switching with Intensity Control Using Arduino UNO works based on sensor inputs and automatic control using a microcontroller. The system uses an LDR sensor to detect surrounding light intensity and an IR sensor to detect approaching vehicles. The Arduino UNO processes the sensor signals and controls the LED headlights according to the programmed conditions.

V. EXPECTED RESULT

The expected result of the project "Smart Vehicle Head Lighting and Auto Switching with Intensity Control Using Arduino UNO" is to develop an intelligent automatic headlight control system that improves road safety, visibility, and driving comfort during night-time driving.

VI. CONCLUSION

The project "Smart Vehicle Head Lighting and Auto Switching with Intensity Control Using Arduino UNO" is designed to improve vehicle safety and driving comfort, especially during night-time driving. The system uses an Arduino UNO microcontroller along with LDR and IR sensors to detect surrounding light conditions and approaching vehicles.

Overall, this project demonstrates the application of embedded systems and sensor-based automation in automobile technology. In the future, the system can be further improved by using advanced sensors, cameras, artificial

IJARSCT
International Journal of Advanced Research in Science, Communication and Technology
International Open-Access, Double-Blind, Peer-Reviewed, Refereed, Multidisciplinary Online Journal
ISSN: 2581-9429
Volume 6, Issue 3, November 2026
Impact Factor: 8.2

intelligence, and adaptive lighting technology to provide more accurate vehicle detection and intelligent headlight control.

VII. ACKNOWLEDGMENT

The authors would like to thank the guide, Mr.Vinay Kumar , the project coordinators, and the Head of the Department of Electrical and Electronics Engineering, Rao Bahadur Y. Mahabaleshwarappa Engineering College, Ballari, for their guidance and support.

REFERENCES

Books :

1.Arduino Programming Book – Simon Monk, Programming Arduino: Getting Started with Sketches.
2.Muhammad Ali Mazidi, The AVR Microcontroller and Embedded Systems.
3.Electronic Devices and Circuit Theory – Robert L. Boylestad